

FIELD CHANGES NOT REQUIRING REVISIONS

Hamilton County Planning and Development, Room 801 County Administration Building (513) 946-4550

All of the following items or changes require a letter from the Owner specifically addressing the changes to the approved documents. Professionally sealed drawings shall be built as drawn and approved. Changes will require revisions.

1. Increased footing sizes and thickness - provided Figure R403.1(1) is complied with.
As long as noted in inspection records
2. Any load-bearing opening requiring sawn lumber wood headers added to wall complying with Table R502.5(1) and Table 502.5(2).
As long as noted in inspection records
3. Additional basement exterior wall framing complying with Table R602.3(5), Table R602.3.1(2) and Table R602.3.1(3) braced complying with Section R602.10.
As long as noted in inspection records
4. Cripple walls not less than 14 inches tall and not exceeding 48" tall complying with Section R602.9.
5. Stepped concrete foundation walls with less than 4 feet of backfill against them.
As long as noted in inspection records
6. Added doors not including walkouts, (provided with complying structural headers) and landings per Section R311.4.3 and still complies with ResCheck (energy analysis)
As long as noted in inspection records
7. Added windows, with complying headers, when ResCheck (energy analysis).
As long as noted in inspection records
8. Moved windows or doors (within the same room).
As long as noted in inspection records
9. Moved interior doors.
As long as noted in inspection records
10. Increased rafter, ceiling joists, and ridge member sizes with no change in center to spacing.
As long as noted in inspection records
11. Balloon framed walls complying with Table R602.3.1(2) and Table R602.3.1(3).

As long as noted in inspection records

12. ResCheck (energy analysis) revisions as long as it still passes.
As long as noted in inspection records
13. Stud wall changes with appropriate spacings.
As long as noted in inspection records
14. Solutions regarding missed or deleted sill plate anchorage.
As long as noted in inspection records